

The SAXO range, known for its exceptional "weight/power" ratio, is suitable for any maintenance activities and everyday intervention operations.

Specification

- Professional : compatible with motor generators.
- Reliable and safe : 1 + 1 year warranty (with registration).
- Easy-to-use : excellent arc striking and stability thanks to the Hot Start, Arc Force and Anti Stick functions.
- Power supply : 230 V single-phase.
- Ultra light : less than 3.8 kg.
- Ready for use : delivered with case and accessories.



Technical features

SAXO 3.2	
Power supply	230 V +/- 15% 50-60 Hz
Effective primary consumption	11 A
Max primary consumption	35 A
No load voltage	69 V
Secondary current range	10-150 A
DutyCycle 10mn 40°C at 35%	150 A @ 10%
DutyCycle 10mn 40°C at 60%	70 A
DutyCycle 10mn 40°C at 100%	55 A
Control connection	9 mm
Consumable Diameter Range	1.6 - 3.2 mm
Protection index	IP 23S
Protection class	H
Equipment free field #1	Max. absorbed power : 4.8 KW
Dimensions (LxIxH) mm	220 x 120 x 320
Weight kg	3.8
Standard	EN 60974-1 / EN 60974-10

» Delivery equipment

Equipped with welding cables, mask, hammer-brush, tool case, diameter 2.5 mm electrode small pack.

» Items codes

W000385239 - SAXO 3.2 1PH 230V

» Environnement & protections

W000276910 - CHAMELEON V0
W000382261 - BLUE STOPCALOR PLUS